CAMBRIDGE INTERNATIONAL EXAMINATIONS

Cambridge International Advanced Subsidiary and Advanced Level

MARK SCHEME for the October/November 2014 series

9702 PHYSICS

9702/31

Paper 3 (Advanced Practical Skills 1), maximum raw mark 40

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2014 series for most Cambridge IGCSE[®], Cambridge International A and AS Level components and some Cambridge O Level components.



Page 2		Mark Scheme	Syllabus	Paper
	(Cambridge International AS/A Level – October/November 2014	9702	31
(b)		ue of T in the range 1.1s – 1.5s with unit. dence of repeated timings.		[1] [1]
(d)		sets of readings of <i>B</i> and <i>C</i> and time scores 5 marks, five sets score trend –1. Help from Supervisor –1.	es 4 marks	etc. [5]
		nge: 1 – 7 (or 8) and <i>B</i> + <i>C</i> = 8.		[1]
	Eac The	umn headings: ch column heading must contain a quantity and a unit where appropressing the conform to accepted scientific convention e.g. $T^2/B/s^2$, as have a unit.		[1] st
		nsistency: values of <i>t</i> must be given to either the nearest 0.1s or 0.01s.		[1]
		nificant figures: values of T^2/B must be given to the same s.f. as (or one more than)	the s.f. in ra	[1] aw <i>t</i> .
		culation: ues of T^2/B are calculated correctly.		[1]
(e)	(i)	Axes: Sensible scales must be used. Awkward scales (e.g. 3:10) are not Scales must be chosen so that the plotted points occupy at least haboth <i>x</i> and <i>y</i> directions. Scales must be labelled with the quantity that is being plotted. Scale markings must be no more than three large squares apart.		[1] n grid in
		Plotting: All observations in the table must be plotted on the graph grid, exceed Diameter of plots must be ≤ half a small square (no "blobs"). Plotted points must be accurate to within half a small square.	ept <i>B</i> = 0.	[1]
		Quality: All points in the table must be plotted (at least 5) for this mark to be Judge by scatter of all points about a straight line. All points must be less than $\pm 0.05 \mathrm{s}^2$ in the T^2/B direction from a straight		[1]
	(ii)	Line of best fit: Judge by balance of all points on the grid (at least 5) about the can There must be an even distribution of points either side of the line a full length. Allow one anomalous plot only if clearly indicated by the candidate labelled). Lines must not be kinked or thicker than half a small square.	along the	

Mark Scheme

Syllabus

Paper

Page 2

1

Р	age	3	Mark Scheme Syllabus Pap	
			Cambridge International AS/A Level – October/November 2014 9702 31	
		(iii)	Gradient: Sign of gradient must match graph (expect a positive gradient). The hypotenuse of the triangle must be greater than half the length of the drawn line Both read-offs must be accurate to half a small square in both x and y directions. The method of calculation must be correct.	[1]
			y-intercept: Either: Correct read-offs from a point on the line and substituted into $y = mx + c$. Read-offs must be accurate to half a small square in both x and y directions.	[1]
			Or: Correct read-off of the intercept directly from the graph.	
	(f)		alue of F = candidate's gradient. Value of G = candidate's intercept. o not allow a value presented as a fraction.	[1]
		Uı	nit for $F(s^2)$ and $G(s^2)$ correct.	[1]
			[Total	: 20]
2	(a)	(i)	Value of D with unit in range $6.0 \le D \le 10.0$ mm.	[1]
		(ii)	Value of d with unit to the nearest 0.01 or 0.001 mm in the range 0.14 to 0.16 mm.	[1]
		(iii)	Correct calculation of $(D + d/2)$.	[1]
	(b)	(ii)	Value of (n + t): Whole number Representation of part of a turn as a decimal or as a fraction	[1] [1]
		(iii)	If repeated readings have been taken, then the uncertainty can be half the range (but not zero) if the working is clearly shown.	[4]
			Correct method of calculation to get percentage uncertainty.	[1]
	(c)	Se	econd value of d . Evidence of repeated readings here or in (a)(ii) econd value of $(n + t)$. econd value of $(n + t)$ < first value of $(n + t)$.	[1] [1] [1]
	(d)	(i)	Correct calculation of two values of <i>k</i> .	[1]
		(ii)	Justification of s.f. in k linked to raw data in D , d and $(n + t)$.	[1]
		(iii)	Valid conclusion based on the calculated values of k , testing against a stated criterion.	[1]

Mark Scheme

Syllabus

Paper

Page 3

Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – October/November 2014	9702	31

(e)	(i) Limitations (4 max.)	(ii) Improvements (4 max.)	Do not credit
Α	Two readings not enough to draw a conclusion.	Take many readings (for different diameters) <u>and</u> plot a graph / compare k values.	repeat readings/few readings
В	Difficult to judge fractions of a turn	Improved method to measure the fraction of a turn e.g. have appropriate markings on rod. e.g. measure spare length and work out as a fraction of the circumference of the rod. e.g. 50/circumference.	
С	Wire slips from start position/springs away from rod.	Method to prevent wire moving e.g. tape/Blu-tack/attach weight/clamp wire on rod.	Wire unstable
D	Length not exactly 50 cm with reason e.g. kinks	Method to straighten wire e.g. apply load or improved method to cut e.g. use tape and knife or use thinner wire for second wire	
E	Thicker wire occupies a longer part of the rod so there are fewer turns/angle of turn of wire affects $(n+t)$ /difficult to make turns touch along the rod	Improved method of placing turns close together e.g. use motor to turn rod.	
F	The values of $(n + t)$ are close together.	Use a thinner rod.	

[Total: 20]