CAMBRIDGE INTERNATIONAL EXAMINATIONS

GCE Advanced Subsidiary Level and GCE Advanced Level

MARK SCHEME for the October/November 2012 series

9702 PHYSICS

9702/43

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2012 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.



Page 2	Mark Scheme	Syllabus	Paper
	GCE AS/A LEVEL – October/November 2012	9702	43

Section A

1 **B1** (a) (i) number of molecules [1] **B**1 [1] (ii) mean square speed **(b) (i) 1.** pV = nRTC1 $n = (6.1 \times 10^5 \times 2.1 \times 10^4 \times 10^{-6}) / (8.31 \times 285)$ C1 $n = 5.4 \, \text{mol}$ **A1** [3] 2. either $N = nN_A$ $= 5.4 \times 6.02 \times 10^{23}$ C1 $= 3.26 \times 10^{24}$ **A1** pV = NkT $N = (6.1 \times 10^5 \times 2.1 \times 10^4 \times 10^{-6}) / (1.38 \times 10^{-23} \times 285)$ (C1) $N = 3.26 \times 10^{24}$ (A1)[2] (ii) either $6.1 \times 10^5 \times 2.1 \times 10^{-2} = \frac{1}{3} \times 3.25 \times 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 4 \times 1.66 \times 10^{-27} \times < c^2 > 10^{24} \times 10^{-27} \times < c^2 \times 10^{-27} \times < c^$ C1 $\langle c^2 \rangle = 1.78 \times 10^6$ C1 $c_{\rm RMS} = 1.33 \times 10^3 \,\mathrm{m \, s^{-1}}$ Α1 $\frac{1}{1/2} \times 4 \times 1.66 \times 10^{-27} \times (c^2) = \frac{3}{2} \times 1.38 \times 10^{-23} \times 285$ (C1) $\langle c^2 \rangle = 1.78 \times 10^6$ (C1) $c_{\rm RMS} = 1.33 \times 10^3 \, \rm m \, s^{-1}$ (A1)[3] 2 (a) (i) 1. 0.1s, 0.3s, 0.5s, etc (any two) **A1** [1] 2. either 0, 0.4 s, 0.8 s, 1.2 s 0.2s, 0.6s, 1.0s (any two) **A1** [1] C1 (ii) period = 0.4sfrequency = (1/0.4 =) 2.5 HzΑ1 [2] (iii) phase difference = 90° or $\frac{1}{2}$ π rad **B**1 [1] **(b)** frequency = $2.4 - 2.5 \,\text{Hz}$ **B1** [1] (c) e.g. attach sheet of card to trolley M1 Α1 increases damping / frictional force e.g. reduce oscillator amplitude (M1)

(A1)

[2]

reduces power/energy input to system

		J	GCE AS/A LEVEL – October/November 2012	9702	43	
3	(a)	(i)	B1	[1]		
		(ii)	M1 A1	[2]		
	(b)	e.g line gre field	nilarity: g. radial fields es normal to surface eater separation of lines with increased distance from sphere d strength $\propto 1$ / (distance to centre of sphere) ² low any sensible answer)	e	B1	
		e.g ele awa e.g ele	Ference: J. gravitational force (always) towards sphere J. gravitational force (always) towards sphere J. gravitational field/force is attractive J. gravitational field/force or repulsive J. gravitational field/force is attractive J. gravitational field/force is attractive J. gravitational field/force is attractive J. gravitational field/force is attractive or repulsive J. gravitational field/force is attractive or repulsive	towards or	B1 B1 (B1) (B1)	[3]
	(c)	ele	exitational force = $1.67 \times 10^{-27} \times 9.81$ = 1.6×10^{-26} N extric force = $1.6 \times 10^{-19} \times 270$ / (1.8×10^{-2}) = 2.4×10^{-15} N extric force very much greater than gravitational force		A1 C1 A1 B1	[4]
4	(a)		ce on proton is normal to velocity and field ovides centripetal force (for circular motion)		M1 A1	[2]
	(b)	cer v = Bq	ignetic force = Bqv intripetal force = $mr\omega^2$ or mv^2/r is $r\omega$ $v = Bqr\omega = mr\omega^2$		B1 B1 B1	
		ω=	= Bq/m		A1	[4]
5	(a)	who θ is θ	ther $\phi = BA \sin \theta$ ere A is the area (through which flux passes) is the angle between B and (plane of) A is BA		M1 A1 (M1)	
		,	ere A is area normal to B		(M1) (A1)	[2]
	(b)	_	aph: $V_{\rm H}$ constant and non zero between the poles and zero carp increase/decrease at ends of magnet	outside	M1 A1	[2]

Mark Scheme

Syllabus

Paper

Page 3

	Page 4				Syllabus		•
				GCE AS/A LEVEL – October/November 2012	9702	43	
	(c)	(i)		d) e.m.f. proportional to change of (magnetic) flux (linkage)		M1 A1	[2]
		(ii)	pulses	ulse on entering and on leaving region between pole approximately the same shape but opposite polaritie ero between poles and outside		M1 A1 A1	[3]
6	(a)	(i)	connec	tion to 'top' of resistor labelled as positive		B1	[1]
		(ii)	diode B	and diode D		B1	[1]
	(b)	(i)	$V_P = 4.0$ mean p = $4^2 / (2^2 + 1)^2$	$0V$ sower = $V_P^2/2R$ 2×2700)		C1 C1	
			= 2.96	× 10 ⁻³ W [′]		A1	[3]
		(ii)	capacito	or, correct symbol, connected in parallel with R		B1	[1]
	(c)) graph: half-wave rectification same period and same peak value					[2]
7	` '		velength is movii	associated with a particle ng		M1 A1	[2]
	(b)	(i)	kinetic e	energy = 1.6 × 10 ⁻¹⁹ × 4700 = 7.52 × 10 ⁻¹⁶ J		C1	
			either e $p = \sqrt{7}$	energy = $p^2/2m$ or $E_K = \frac{1}{2}mv^2$ and $p = mv$ $.52 \times 10^{-16} \times 2 \times 9.1 \times 10^{-31}$) $\times 10^{-23} \text{ N s}$		C1 C1	
			$\lambda = h/p$			C1	
			= (6.6 = 1.8	63×10^{-34}) / (3.7 × 10 ⁻²³) × 10 ⁻¹¹ m		A1	[5]
		(ii)		ngth is about separation of atoms used in (electron) diffraction		B1 B1	[2]
8	(a)	(i)	<i>x</i> = 2			A1	[1]
		(ii)	<i>either</i> b	eta particle <i>or</i> electron		B1	[1]
	(b)	(i)		f separate nucleons = {(92 × 1.007) + (143 × 1.009)} = 236.931 u	} u	C1 C1	
			binding	energy = 236.931 u - 235.123 u = 1.808 u		A1	[3]

	Page 5		j	Mark Scheme	Syllabus	Paper	•	
				GCE AS/A LEVEL – October/November 2012	9702	43		
		(ii) $E = mc^2$ energy = 1.808 × 1.66 × 10 ⁻²⁷ × $(3.0 \times 10^8)^2$						
	$= 2.7 \times 10^{-10} \text{ J}$ binding energy per nucleon = $(2.7 \times 10^{-10}) / (235 \times 1.6 \times 10^{-13})$ $= 7.18 \text{ MeV}$							
							[3]	
		= 7.10 IVIEV						
	(c)	ene	ergy re	eleased = (95 × 8.09) + (139 × 7.92) - (235 × 7.18) = 1869.43 - 1687.3		C1		
		, ,,		= 182 MeV		A1	[2]	
		(all	ow ca	lculation using mass difference between products and	reactants)			
				Section B				
9	(a)	ligh	t-emi	tting diode (<i>allow LED</i>)		B1	[1]	
	(b)	aive	es a h	igh or a low output / +5V or –5V output		M1		
	(,	_		nt on which of the inputs is at a higher potential		A1	[2]	
	(c)	(i)	prov	ides a reference/constant potential		B1	[1]	
	(0)		•	·				
		(ii)	dete	rmines temperature of 'switch-over'		B1	[1]	
	(d)	(i)	relay	<i>'</i>		A1	[1]	
		(ii)	-	connected correctly for op-amp output and high-volta e with correct polarity in output from op-amp	ge circuit	B1 B1	[2]	
			ulou	e with correct polarity in output from op-amp		ы	[4]	
10	(a)	bac	kgrou	und reading = 19		B1	[1]	
	(h)	A =	. 2			A1		
	(6)	B =	5			A1		
		C =				A1	F 4 1	
		D = (<i>All</i>		mark if only subtracts background reading)		A1	[4]	
	(0)	(i)	oithe	or 5 14 or 14 5 (A+D B+C or v.v.)		B1	[41	
	(c)			er 5, 14 or 14, 5 (A+D, B+C or v.v.)			[1]	
		(ii)		ee numbers and 'inside' number is 8 (B+D) ee numbers and 'outside' numbers are <i>either</i> 2,9 <i>or</i> 9,2	(A,C or <i>v.v.</i>)	B1 B1	[2]	
11	(a)			uency wave itude or the frequency is varied		B1 M1		
		the	varia	tion represents the information signal /				
		ın s	ynchr	rony with (the displacement of) the information signal.		A1	[3]	

Page 6		6	Mark Scheme	Syllabus	Paper		
			GCE AS/A LEVEL – October/November 2012 9702			43	
	(b) e.g. shorter aerial required longer transmission range / lower transmitter power / less attenuation allows more than one station in a region less distortion (allow any three sensible suggestions, 1 mark each)						[3]
12	(a)	(i)	e.g.	linking a (land) telephone to the (local) exchange		В1	[1]
		(ii)	e.g.	connecting an aerial to a television		B1	[1]
	((iii)	e.g.	linking a ground station to a satellite		B1	[1]
	(b)	(i)	total 84 = P =	nuation = $10 \lg (P_2 / P_1)$ attenuation = $2.1 \times 40 (= 84 dB)$ $10 \lg (\{450 \times 10^{-3}\} / P)$ $1.8 \times 10^{-9} W$ wer $1.1 \times 10^8 W$ scores 1 mark only)		C1 C1 A1	[3]
		(ii)		imum attenuation = $10 \lg (\{450 \times 10^{-3}\} / \{7.2 \times 10^{-11}\})$ = $98 dB$ imum length = $98/2.1$ = 47 km		C1 A1	[2]