UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS

GCE Advanced Subsidiary Level and GCE Advanced Level

MARK SCHEME for the October/November 2008 question paper

9702 PHYSICS

9702/04

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began.

All Examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the October/November 2007 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



| Pac | ge 2 | Mark Scheme | Syllabus | Pape | r |
|------|-------|--|----------|----------------|----------|
| | | GCE A/AS LEVEL – October/November 2008 9702 | | 04 | |
| ctio | n A | | | | |
| (a) | (i) | $F = GMm / R^2$ | | B1 | [1 |
| | (ii) | $F = mR\omega^2$ | | B1 | [1 |
| | (iii) | reaction force = $GMm / R^2 - mR\omega^2$ (allow e.c.f.) | | B1 | [1 |
| (b) | (i) | either value of R in expression $R\omega^2$ varies or $mR\omega^2$ no longer parallel to GMm / R^2 / normal becomes smaller as object approaches a pole / is zero | | B1 B1 | [2 |
| | (ii) | 1. acceleration = $6.4 \times 10^6 \times (2\pi / \{8.6 \times 10^4\})^2$ = 0.034 m s ⁻² 2. acceleration = 0 | | C1 A1 A1 | [2 [1 |
| (c) | e.g | . 'radius' of planet <u>varies</u> density of planet <u>not constant</u> planet spinning nearby planets / stars (any sensible comments, 1 mark each, maximum 2) | | B2 | [2 |
| (a) | àt it | ermal) energy / heat required to convert unit mass of sts normal melting point / without any change in temperaterence to 1 kg or to ice → water scores max 1 mark) | - | M1 A1 | [2 |
| (b) | (i) | To make allowance for heat gains from the atmosphe | ere | B1 | [1 |
| | (ii) | e.g. constant rate of production of droplets from funne constant mass of water collected per minute in beake (any sensible suggestion, 1 mark) | | B1 | [1 |
| | (iii) | mass melted by heater in 5 minutes = $64.7 - \frac{1}{2} \times 16.6$ $56.4 \times 10^{-3} \times L = 18$ $L = 320$ kJ kg ⁻¹ (Use of $m = 64.7$, giving $L = 278$ kJ kg ⁻¹ , scores max use of $m = 48.1$, giving $L = 374$ kJ kg ⁻¹ , scores max 2 | 1 mark | C1 C1 A1 | [3 |
| (a) | | releration / force (directly) proportional to displacement deither directed towards fixed point | | M1 | |
| | | or acceleration & displacement in opposite direction | าร | A1 | [|

[1]

[1]

[2]

В1

Α1

C1

Α1

(b) (i) maximum / minimum height / 8 mm above cloth / 14 mm below cloth

= 28.3 rad s^{-1} (do not allow 1 s.f.)

(ii) 1. a = 11 mm

2. $\omega = 2\pi f$

= $2\pi \times 4.5$

| Page 3 | | | | Syllabus | Paper | |
|--------|----|--------------|--|----------------------|----------------|-----|
| | | | GCE A/AS LEVEL – October/November 2008 | 9702 | 04 | |
| (| c) | (i) | $v = \omega a$ $= 28.3 \times 11 \times 10^{-3}$ | | C1 | |
| | | 410 | = 0.31 m s ⁻¹ (do not allow 1 s.f.) | | A1 | [2] |
| | | | $v = \omega \sqrt{(a^2 - y^2)}$ y = 3 mm | | C1 | |
| | | | = $28.3 \times 10^{-3} \sqrt{(11^2 - 3^2)}$ = 0.30 m s^{-1} (allow 1 s.f.) | | C1 A1 | [3] |
| 4 (| a) | Δ <i>U</i> = | = q + w (allow correct word equation) | | B1 | [1] |
| (1 | b) | eithe | er kinetic energy constant because temperature constant potential energy constant because no intermolecular for so no change in internal energy | | M1 M1 A1 | [3] |
| | | or | so no change in internal energy | (M1) (A1) (A1) | | |
| 5 (| | 2 × ½ | nge/loss in kinetic energy = change/gain in electric potential $\frac{1}{2}mv^2 = q^2 / 4\pi\varepsilon_0 r$ | l energy | B1 C1 | |
| | | | $\frac{1}{2} \times 2 \times 1.67 \times 10^{-27} \times v^2$ = $(1.6 \times 10^{-19})^2 / (4\pi \times 8.85 \times 10^{-12} \times 1.1 \times 10^{-14})$ $2.5 \times 10^6 \text{ m s}^{-1}$ | | M1 A0 | [3] |
| (1 | | | = $\frac{1}{2}Nm < c^2 >$ and $pV = NkT$ | | C1 | |
| | | ½ m | $ = \frac{3}{2} kT$ (award 1 mark of first two if $$ not used) | | C1 | |
| | | | $2 \times 1.67 \times 10^{-27} \times (2.5 \times 10^{6})^{2} = \frac{3}{2} \times 1.38 \times 10^{-23} \times T$ 5 × 10 ⁸ K | | C1 A1 | [4] |
| (| c) | | this is <u>very</u> high temperature temperature found in stars (any sensible comment, 1 mark) (if $T < 10^6$ K, should comment that too low for fusion to occ | ur | B1 | [4] |
| | | | (II T < TO TK, SHOULD COMMENT THAT TOO TOW TOT TUSTOM TO OCC | ur) | ы | [1] |
| 6 (| a) | | either prevent loss of magnetic flux or improves flux linkage with secondary | | B1 | [1] |
| | | | reduces eddy current (losses) reduces losses of energy (in core) | | B1 B1 | [2] |
| (1 | b) | | (induced) e.m.f. proportional to / equal to rate of change of (magnetic) flux (linkage) | | M1 A1 | [2] |
| | | | changing current in primary gives rise to (1) changing flux in core (1) flux links with the secondary coil (1) changing flux in secondary coil, inducing e.m.f. (1) | | | |

| | Page 4 | | Mark Scheme Sylla | | Pape | Paper | |
|---|--------|-------|--|--------|----------------|------------|--|
| | | | GCE A/AS LEVEL – October/November 2008 9702 | | 04 | | |
| | (c) | | (any three, 1 each to max 3) can change voltage easily / efficiently high voltage transmission reduces power losses / two sensible suggestions, 1 each) | | B3 B2 | [3] [2] | |
| 7 | (a) | | 'instantaneous' emission (of electrons) threshold frequency below which no emission (max) electron energy dependent on frequency (max) electron energy not dependent on intensity rate of emission (of electrons) depends on intensity / three sensible suggestions, 1 each) | | В3 | [3] | |
| | (b) | (i) | 'packet' / quantum of energy of electromagnetic energy / radiation | | M1 A1 | [2] | |
| | | (ii) | discrete wavelengths mean photons have particular energy of photon determined by energy change of (o so discrete energy levels | · · | M1 M1 A0 | [2] | |
| | (c) | (i) | three energy changes shown correctly arrows 'pointing' in correct direction wavelengths correctly identified | | B1 B1 B1 | [3] | |
| | | (ii) | chooses $\lambda = 486 \text{ nm}$ $\Delta E = hc / \lambda$ = $(6.63 \times 10^{-34} \times 3.0 \times 10^{8}) / (4.86 \times 10^{-9})$ = $4.09 \times 10^{-19} \text{ J}$ (allow 2 s.f.) | | C1 C1 A1 | [3] | |
| 8 | (a) | a fo | on (of space) / area where rce is experienced by ent-carrying conductor / moving charge / permanent r | magnet | B1 M1 A1 | [3] | |
| | (b) | (i) | electric | | B1 | [1] | |
| | | (ii) | gravitational | | B1 | [1] | |
| | | (iii) | magnetic | | B1 | [1] | |
| | | (iv) | magnetic | | B1 | [1] | |

| Page 5 | Mark Scheme | Syllabus | Paper |
|-----------|--|----------|-------|
| | GCE A/AS LEVEL – October/November 2008 | 9702 | 04 |
| Section B | | | |

9 **B1** (a) IR has less attenuation (per unit length) **B1** [2] fewer (repeater) amplifiers / longer uninterrupted length **(b)** *either* limited range **B**1 (so) cells do not overlap (appreciably) **B**1 [2] short wavelength (B1) or so convenient length aerial (on mobile phone) (B1) (c) large bandwidth / large information carrying capacity В1 different so that uplink signal not swamped by downlink **B1** [2] 10 (a) (i) 1. inverting (amplifier) **B1** [1] 2. gain of op-amp is very large / infinite **B1 B1** non-inverting input is at earth / 0 V for amplifier not to saturate, P must be at about earth / 0 V **B**1 [3] (ii) input resistance is very large **B1** (so) current in R_1 = current in R_2 **B1** $I = V_{IN} / R_1$ **B1** $I = -V_{OUT}/R_2$ (minus sign can be in either of the equations) **B**1 hence gain = $V_{OUT} / V_{IN} = -R_2 / R_1$ Α0 [4] (b) (i) 1. feedback resistance = $33.3 \text{ k}\Omega$ C₁ C1 gain (= 33.3 / 5) = 6.66 V_{OUT} (= 6.66 × 1.2) = 8.0 V (+ or – acceptable, allow 1 s.f.) Α1 [3] **2.** feedback resistance = $8.33 \text{ k}\Omega$ C1 V_{OUT} (= $\{6.66 \times 1.2\} / 5$) = 2.0 V (+ or – acceptable, allow 1 s.f.) Α1 [2] (ii) (Increase in lamp-LDR distance gives) decrease in intensity M1 M1 Feedback / LDR resistance increases voltmeter reading increases / becomes more negative Α1 [3] **11 (a)** CT image: (thin) slice (through structure) **B1** any further detail e.g. built up from many 'slices' / 3-D image **B1** X-ray image: 'shadow' image (of whole structure) / 2-D image B1 [3] **(b)** X-ray image of slice taken from many different angles (1)these images are combined (and processed) (1)repeated for many different slices (1) to build up a 3-D image (1)3-D image can be rotated (1)computer required to store and process huge quantity of data (1)

B5

[5]

(any five, 1 each to max 5)