

**MARK SCHEME for the May/June 2010 question paper
for the guidance of teachers**

9702 PHYSICS

9702/43

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

- CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the May/June 2010 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2010	9702	43

Section A

- 1 (a) work done moving unit mass from infinity to the point M1
A1 [2]
- (b) (i) at R , $\phi = 6.3 \times 10^7 \text{ J kg}^{-1}$ (allow $\pm 0.1 \times 10^7$) B1
 $\phi = GM / R$
 $6.3 \times 10^7 = (6.67 \times 10^{-11} \times M) / (6.4 \times 10^6)$ C1
 $M = 6.0 \times 10^{24} \text{ kg}$ (allow $5.95 \rightarrow 6.14$) A1 [3]
Maximum of 2/3 for any value chosen for ϕ not at R
- (ii) change in potential = $2.1 \times 10^7 \text{ J kg}^{-1}$ (allow $\pm 0.1 \times 10^7$) C1
loss in potential energy = gain in kinetic energy B1
 $\frac{1}{2} mv^2 = \phi m$ or $\frac{1}{2} mv^2 = GM / 3R$ C1
 $\frac{1}{2} v^2 = 2.1 \times 10^7$
 $v = 6.5 \times 10^3 \text{ m s}^{-1}$ (allow $6.3 \rightarrow 6.6$) A1 [4]
(answer $7.9 \times 10^3 \text{ m s}^{-1}$, based on $x = 2R$, allow max 3 marks)
- (iii) e.g. speed / velocity / acceleration would be greater B1
deviates / bends from straight path B1 [2]
(any sensible ideas, 1 each, max 2)
- 2 (a) (i) reduction in energy (of the oscillations) (B1)
reduction in amplitude / energy of oscillations (B1)
due to force (always) opposing motion / resistive forces (B1) [2]
any two of the above, max 2
- (ii) amplitude is decreasing (very) gradually / oscillations would M1
continue (for a long time) / many oscillations A1 [2]
light damping
- (b) (i) frequency = $1 / 0.3$ A1 [1]
= 3.3 Hz
allow points taken from time axis giving $f = 3.45 \text{ Hz}$
- (ii) energy = $\frac{1}{2} mv^2$ and $v = \omega a$ C1
= $\frac{1}{2} \times 0.065 \times (2\pi/0.3)^2 \times (1.5 \times 10^{-2})^2$ M1
= 3.2 mJ A0 [2]
- (c) amplitude reduces exponentially / does not decrease linearly M1
so will be not be 0.7 cm A1 [2]

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2010	9702	43

- 3 (a) (i) 1 deg C corresponds to $(3840 - 190) / 100 \Omega$ C1
for resistance 2300 Ω , temperature is $100 \times (2300 - 3840) / (190 - 3840)$
temperature is 42 °C A1 [2]
- (ii) *either* 286 K \equiv 13 °C *or* 42 °C \equiv 315 K B1
thermodynamic scale does not depend on the property of a substance M1
so change in resistance (of thermistor) with temperature is non-linear A1 [3]
- (b) heat gained by ice in melting = $0.012 \times 3.3 \times 10^5$ J C1
= 3960 J
heat lost by water = $0.095 \times 4.2 \times 10^3 \times (28 - \theta)$ C1
 $3960 + (0.012 \times 4.2 \times 10^3 \times \theta) = 0.095 \times 4.2 \times 10^3 \times (28 - \theta)$ C1
 $\theta = 16^\circ\text{C}$ A1 [4]
(answer 18°C – melted ice omitted – allow max 2 marks)
(use of $(\theta - T)$ then allow max 1 mark)
- 4 (a) force = $q_1q_2 / 4\pi\epsilon_0x^2$ C1
= $(6.4 \times 10^{-19})^2 / (4\pi \times 8.85 \times 10^{-12} \times \{12 \times 10^{-6}\}^2)$ C1
= 2.56×10^{-17} N A1 [3]
- (b) potential at P is same as potential at Q B1
work done = $q\Delta V$ M1
 $\Delta V = 0$ so zero work done A0 [2]
- (c) at midpoint, potential is $2 \times (6.4 \times 10^{-19}) / (4\pi\epsilon_0 \times 6 \times 10^{-6})$ C1
at P, potential is $(6.4 \times 10^{-19}) / (4\pi\epsilon_0 \times 3 \times 10^{-6}) + (6.4 \times 10^{-19}) / (4\pi\epsilon_0 \times 9 \times 10^{-6})$ C1
change in potential = $(6.4 \times 10^{-19}) / (4\pi\epsilon_0 \times 9 \times 10^{-6})$
energy = $1.6 \times 10^{-19} \times (6.4 \times 10^{-19}) / (4\pi\epsilon_0 \times 9 \times 10^{-6})$ C1
= 1.0×10^{-22} J A1 [4]
- 5 (a) e.g. 'storage of charge' / storage of energy
blocking of direct current
producing of electrical oscillations
smoothing
(any two, 1 mark each) B2 [2]
- (b) (i) capacitance of parallel combination = 60 μF C1
total capacitance = 20 μF A1 [2]
- (ii) p.d. across parallel combination = $\frac{1}{2} \times$ p.d. across single capacitor C1
maximum is 9V A1 [2]
- (c) *either* energy = $\frac{1}{2}CV^2$ *or* energy = $\frac{1}{2}QV$ and $Q = CV$ C1
energy = $\frac{1}{2} \times 4700 \times 10^{-6} \times (18^2 - 12^2)$ C1
= 0.42 J A1 [3]

Page 4	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2010	9702	43

- 6 (a) (i) straight line with positive gradient through origin M1
A1 [2]
- (ii) maximum force shown at $\theta = 90^\circ$ M1
zero force shown at $\theta = 0^\circ$ M1
reasonable curve with F about $\frac{1}{2}$ max at 30° A1 [3]
- (b) (i) force on electron due to magnetic field B1
force on electron normal to magnetic field and direction of electron B1 [2]
- (ii) quote / mention of (Fleming's) left hand rule M1
electron moves towards QR A1 [2]
- 7 (a) *either* the value of steady / constant voltage M1
that produces same power (in a resistor) as the alternating voltage A1 [2]
or if alternating voltage is squared and averaged (M1)
the r.m.s. value is the square root of this averaged value (A1)
- (b) (i) 220 V A1 [1]
- (ii) 156 V A1 [1]
- (iii) 60 Hz A1 [1]
- (c) power = V_{rms}^2 / R C1
 $R = 156^2 / 1500$
 $= 16 \Omega$ A1 [2]
- 8 (a) (i) number = $(5.1 \times 10^{-6} \times 6.02 \times 10^{23}) / 241$ C1
 $= 1.27 \times 10^{16}$ A1 [2]
- (ii) $A = \lambda N$ C1
 $5.9 \times 10^5 = \lambda \times 1.27 \times 10^{16}$
 $\lambda = 4.65 \times 10^{-11} \text{ s}^{-1}$ A1 [2]
- (iii) $4.65 \times 10^{-11} \times t_{1/2} = \ln 2$ C1
 $t_{1/2} = 1.49 \times 10^{10} \text{ s}$
 $= 470 \text{ years}$ A1 [2]
- (b) sample / activity would decay appreciably whilst measurements are being made B1 [1]

Page 5	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2010	9702	43

Section B

- 9 (a) (i)** fraction of the output (signal) is added to the input (signal)
out of phase by $180^\circ / \pi$ rad / to inverting input M1
A1 [2]
- (ii)** e.g. reduces gain
increases bandwidth
greater stability
reduces distortion
(any two, 1 mark each) B2 [2]
- (b) (i)** gain = $4.4 / 0.062$
= 71 A1 [1]
- (ii)** $71 = 1 + 120/R$ C1
 $R = 1.7 \times 10^3 \Omega$ A1 [2]
- (c)** for the amplifier not to saturate B1
maximum output is ($71 \times 95 \times 10^{-3} =$) approximately 6.7 V M1
supply should be ± 9 V A1 [3]
- 10 (a) (i)** strain gauge B1 [1]
- (ii)** piezo-electric / quartz crystal / transducer B1 [1]
- (b)** circuit: coil of relay connected between sensing circuit output and earth B1
switch across terminals of external circuit B1
diode in series with coil with correct polarity for diode B1
second diode with correct polarity B1 [4]
- 11** *either* quartz *or* piezo-electric crystal B1
opposite faces /two sides coated (with silver) to act as electrodes B1
either molecular structure indicated
or centres of (+) and (–) charge not coincident B1
potential difference across crystal causes crystal to change shape B1
alternating voltage (in US frequency range) applied across crystal B1
causes crystal to oscillate / vibrate B1
(crystal cut) so that it vibrates at resonant frequency B1 [6]
(max 6)

Page 6	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2010	9702	43

- 12 (a) signal becomes distorted / noisy B1
 signal loses power / energy / intensity / is attenuated B1 [2]
- (b) (i) *either* numbers involved are smaller / more manageable / cover wider range
or calculations involve addition & subtraction rather than multiplication and division B1 [1]
- (ii) $25 = 10 \lg(P_{\min} / (6.1 \times 10^{-19}))$ C1
 minimum signal power = 1.93×10^{-16} W C1
 signal loss = $10 \lg(6.5 \times 10^{-3} / (1.93 \times 10^{-16}))$
 = 135 dB C1
 maximum cable length = $135 / 1.6$ C1
 = 85 km so no repeaters necessary A1 [5]