## Cambridge International Examinations International AS & A Level



## READ THESE INSTRUCTIONS FIRST

Write your Centre number, candidate number and name in the spaces at the top of this page. Write in dark blue or black pen. You may use an HB pencil for any diagrams, graphs or rough working. Do not use staples, paper clips, glue or correction fluid. DO **NOT** WRITE IN ANY BARCODES.

Answer **all** questions. No marks will be awarded for using brand names of software packages or hardware.

At the end of the examination, fasten all your work securely together. The number of marks is given in brackets [] at the end of each question or part question.

The maximum number of marks is 75.

This document consists of 14 printed pages and 2 blank pages.



**1** (a) Consider the following pseudocode user-defined data type:

TYPE MyContactDetail DECLARE Name : STRING DECLARE HouseNumber : INTEGER

ENDTYPE

(i) Write a pseudocode statement to declare a variable, NewFriend, of type MyContactDetail.

.....[1]

(ii) Write a pseudocode statement that assigns 129 to the HouseNumber of NewFriend.

.....[1]

- (b) The user-defined data type MyContactDetail needs to be modified by:
  - adding a field called Area which can take three values, uptown, downtown or midtown
  - amending the field HouseNumber so that house numbers can only be in the range 1 to 499.

Write the updated version of MyContactDetail.

[3]

(c) A pointer is a variable that stores the address of a variable of a particular type.

Consider the pseudocode on page 3, which uses the following identifiers:

Identifier	Data type	Description
IPointer	^INTEGER	pointer to an integer
Sum	INTEGER	an integer variable
MyIntl	INTEGER	an integer variable
MyInt2	INTEGER	an integer variable

Sum ← 91	// assigns the value 91 to the integer variable Sum
IPointer $\leftarrow$ @Sum	// assigns to IPointer the address of the
	// integer variable Sum
MyInt1 🔶 IPointer^	<pre>// assigns to variable MyInt1 the value at an</pre>
	// address pointed at by IPointer
IPointer^ $\leftarrow$ MyInt2	// assigns the value in the variable MyInt2 to
	// the memory location pointed at by IPointer

The four assignment statements are executed. The diagram shows the memory contents after execution.

Variable	Memory Address	Contents
		7
	5848	
	5847	
IPointer	5846	4402
	5845	
		$\sim$
	4403	
Sum	4402	33
	4401	
		(م
	3428	
MyInt1	3427	91
MyInt2	3426	33
	3425	

Use the diagram to state the current values of the following expressions:

(i)	IPointer[1]
(ii)	IPointer^[1]
(iii)	@MyInt1[1]
(iv)	IPointer^ = MyInt2[1]

4

- (d) Write pseudocode statements that will achieve the following:
  - (i) Place the address of MyInt2 in IPointer.
    [1]
    (ii) Assign the value 33 to the variable MyInt1.
    [1]
    (iii) Copy the value in MyInt2 into the memory location currently pointed at by IPointer.
    [1]

- 2 The following incomplete table shows descriptions and terms relating to malware.
  - (a) Complete the table with appropriate description and terms.

	Description	Term
(i)	Malicious code is installed on a personal computer so that the user is misdirected to a fraudulent web site without their knowledge.	
ii)	An attempt to acquire sensitive information, often for malicious reasons, by trying to deceive the user through the contents of an email.	
ii)		
		Worm

(b) State two vulnerabilities that the malware in part (a)(i) or part (a)(ii) can exploit.

Vulnerability 1	 	 	
Vulnerability 2	 	 	
			[2]

(c) Digital certificates are used in internet communications. A Certificate Authority (CA) is responsible for issuing a digital certificate.

The digital certificate contains a digital signature produced by the CA.

- - .....[1]
- **3** A logic circuit is shown:



- (a) Write the Boolean algebraic expression corresponding to this logic circuit:
  - S = .....[4]

Р	Q	R	Working space	S
0	0	0		
0	0	1		
0	1	0		
0	1	1		
1	0	0		
1	0	1		
1	1	0		
1	1	1		

(b) Complete the truth table for this logic circuit:

(c) (i) Complete the Karnaugh Map (K-map) for the truth table in part (b).



The K-map can be used to simplify the function in part (a).

- (ii) Draw loop(s) around appropriate groups to produce an optimal sum-of-products. [1]
  (iii) Write a simplified sum-of-products expression, using your answer to part (ii).
  - S = .....[1]
- (d) One Boolean identity is:

$$(A + B) \cdot C = A \cdot C + B \cdot C$$

Simplify the expression for S in part (a) to the expression for S in part (c)(iii).

You should use the given identity and De Morgan's Laws.

[2]

[1]

4 (a) Three file organisation methods and two file access methods are shown below.

Draw lines to link each file organisation method to its appropriate file access method(s).



(b) An energy company supplies electricity to a large number of customers. Each customer has a meter that records the amount of electricity used. Customers submit meter readings using their online account.

The company's computer system stores data about its customers.

This data includes:

- account number
- personal data (name, address, telephone number)
- meter readings
- username and encrypted password.

The computer system uses three files:

File	Content	Use
A	Account number and meter readings for the current month.	Each time a customer submits their reading, a new record is added to the file.
В	Customer's personal data.	At the end of the month to create a statement that shows the electricity supplied and the total cost.
С	Usernames and encrypted passwords.	When customers log in to their accounts to submit meter readings.

For each of the files A, B and C, state an appropriate file organisation method for the use given in the table.

All three file organisation methods must be different.

Justify your choice.

(i)	File A organisation
	Justification
	[3]
(ii)	File B organisation
	Justification
	[3]
(iii)	File C organisation
	Justification
	[3]

5 The TCP/IP protocol suite can be viewed as a stack with four layers.

Г

(a) Complete the stack by inserting the names of the three missing layers.

	Application layer
	[3]
(b) Bit	orrent is a protocol used at the Application layer for the exchange of data.
(i)	State the network model used with this protocol.
	[1]
(ii)	State the use of BitTorrent.
	[1]
(iii)	Explain how the exchange of data is achieved using BitTorrent.
	[4]

(c) State two additional protocols that are also used at the Application layer for the exchange of data.

For each protocol, give an example of an appropriate exchange of data.

otocol 1	
ample	
otocol 2	
ample	
	[4]

6 A large office building has many floors. On each floor there are security sensors and security cameras. There is the same number of sensors on each floor. The building has a single security room.

The images from the security cameras are output on monitors (one monitor for each floor) placed in the security room.

The data from the sensors are read and processed by a computer system. Sensor readings and warning messages can be displayed on the monitors.

- (a) (i) State the name given to the type of system described.
  - (ii) Explain your answer to part (i).
    (iii) State two sensors that could be used in this system.
    Sensor 1
    Sensor 2
- (b) A software routine:
  - checks the readings from the sensors
  - outputs readings and warning messages to the monitors
  - loops continuously.

The routine uses the following pseudocode variables:

Identifier	Data type	Description
FloorCounter	INTEGER	Loop counter for number of floors
SensorCounter	INTEGER	Loop counter for number of sensors
NumberOfFloors	INTEGER	Stores the number of floors
NumberOfSensors	INTEGER	Stores the number of sensors
ForEver	BOOLEAN	Stores value that ensures continuous loop

(i) Complete the following pseudocode algorithm for the routine.

```
01 ForEver ← .....
   02 REPEAT
      FOR FloorCounter ← 1 TO NumberOfFloors
   03
   04
        FOR SensorCounter \leftarrow 1 TO .....
   05
         READ Sensor(SensorCounter) on Floor(FloorCounter)
   06
         IF Sensor value outside range
   07
           THEN
   80
             OUTPUT "Problem on Floor ", FloorCounter
   09
         ENDIF
   10
      ENDFOR
   11
      ENDFOR
   12
      //
   13
      // Delay loop
   14
      // Delay loop
      11
   15
   16 UNTIL .....
                                               [3]
(ii) A delay needs to be introduced before the loop is processed again.
   Write a FOR loop, in pseudocode, to replace lines 13 and 14.
   .....[1]
(iii) Give a reason for this delay in the system.
   .....
   .....[1]
```

(c) An alternative method of reading and processing sensor data is to use interrupts. Each sensor is connected so that it can send an interrupt signal to the processor if its value changes.

On receipt of an interrupt signal, the processor carries out a number of steps as shown in the following diagram.



## **BLANK PAGE**

## **BLANK PAGE**

Permission to reproduce items where third-party owned material protected by copyright is included has been sought and cleared where possible. Every reasonable effort has been made by the publisher (UCLES) to trace copyright holders, but if any items requiring clearance have unwittingly been included, the publisher will be pleased to make amends at the earliest possible opportunity.

To avoid the issue of disclosure of answer-related information to candidates, all copyright acknowledgements are reproduced online in the Cambridge International Examinations Copyright Acknowledgements Booklet. This is produced for each series of examinations and is freely available to download at www.cie.org.uk after the live examination series.

Cambridge International Examinations is part of the Cambridge Assessment Group. Cambridge Assessment is the brand name of University of Cambridge Local Examinations Syndicate (UCLES), which is itself a department of the University of Cambridge.