
PHYSICS

9702/52

Paper 5 Planning, Analysis and Evaluation

October/November 2018

MARK SCHEME

Maximum Mark: 30

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the October/November 2018 series for most Cambridge IGCSE™, Cambridge International A and AS Level components and some Cambridge O Level components.

This document consists of **8** printed pages.

PUBLISHED**Generic Marking Principles**

These general marking principles must be applied by all examiners when marking candidate answers. They should be applied alongside the specific content of the mark scheme or generic level descriptors for a question. Each question paper and mark scheme will also comply with these marking principles.

GENERIC MARKING PRINCIPLE 1:

Marks must be awarded in line with:

- the specific content of the mark scheme or the generic level descriptors for the question
- the specific skills defined in the mark scheme or in the generic level descriptors for the question
- the standard of response required by a candidate as exemplified by the standardisation scripts.

GENERIC MARKING PRINCIPLE 2:

Marks awarded are always **whole marks** (not half marks, or other fractions).

GENERIC MARKING PRINCIPLE 3:

Marks must be awarded **positively**:

- marks are awarded for correct / valid answers, as defined in the mark scheme. However, credit is given for valid answers which go beyond the scope of the syllabus and mark scheme, referring to your Team Leader as appropriate
- marks are awarded when candidates clearly demonstrate what they know and can do
- marks are not deducted for errors
- marks are not deducted for omissions
- answers should only be judged on the quality of spelling, punctuation and grammar when these features are specifically assessed by the question as indicated by the mark scheme. The meaning, however, should be unambiguous.

GENERIC MARKING PRINCIPLE 4:

Rules must be applied consistently e.g. in situations where candidates have not followed instructions or in the application of generic level descriptors.

GENERIC MARKING PRINCIPLE 5:

Marks should be awarded using the full range of marks defined in the mark scheme for the question (however; the use of the full mark range may be limited according to the quality of the candidate responses seen).

GENERIC MARKING PRINCIPLE 6:

Marks awarded are based solely on the requirements as defined in the mark scheme. Marks should not be awarded with grade thresholds or grade descriptors in mind.

PUBLISHED

Question	Answer	Marks
1	Defining the problem	
	temperature (of the water)/ θ is the independent variable and volume per unit time/ Y is the dependent variable or vary θ and determine Y	1
	keep temperature of room/surroundings <u>constant</u>	1
	Methods of data collection	
	labelled diagram of workable experiment including: <ul style="list-style-type: none"> • beaker open to air • water, labelled • workable method to heat water 	1
	method to determine (change in) volume, e.g. measuring cylinder or method to determine (change in) mass, e.g. top-pan balance	1
	measure time with a <u>stop-watch/timer</u> (for change in volume/mass or evaporation)	1
	use a thermometer to measure θ or labelled thermometer in water in diagram	1
	Method of analysis	
	plot a graph of $\lg Y$ against $\lg \theta$ (or $\ln Y$ against $\ln \theta$)	1
	$s = \text{gradient}$	1
	$k = 10^{\text{y-intercept}}$ (for $\ln Y$ against $\ln \theta$: $k = e^{\text{y-intercept}}$)	1

PUBLISHED

Question	Answer	Marks
	Additional detail including safety considerations	Max. 6
D1	use of (protective) gloves to handle <u>hot</u> beaker/water	
D2	keep surface <u>area constant</u> (by using the same cylindrical container)	
D3	keep water temperature <u>constant</u> (while water is evaporating)	
D4	method to keep temperature constant while water is evaporating e.g. adjust heater/gently heat water to maintain temperature/use a water bath	
D5	use a large surface area to increase the rate of evaporation	
D6	$Y = \frac{\text{initial volume} - \text{final volume}}{\text{time}}$ or $\frac{\Delta V}{\text{time}}$	
D7	$\lg Y = s \lg \theta + \lg k$	
D8	relationship valid if a straight line	
D9	insulation/lagging around (sides) of beaker (not a lid)	
D10	switch off fans or close windows <u>to avoid draughts</u>	

PUBLISHED

Question	Answer	Marks						
2(a)	gradient = $\frac{R}{E}$ y-intercept = $\frac{r}{E}$	1						
2(b)	<table border="1" style="margin-left: 20px;"> <tr><td>29 or 29.4</td></tr> <tr><td>22 or 21.7</td></tr> <tr><td>18 or 17.9</td></tr> <tr><td>15 or 15.2</td></tr> <tr><td>13 or 13.2</td></tr> <tr><td>12 or 11.9</td></tr> </table>	29 or 29.4	22 or 21.7	18 or 17.9	15 or 15.2	13 or 13.2	12 or 11.9	1
29 or 29.4								
22 or 21.7								
18 or 17.9								
15 or 15.2								
13 or 13.2								
12 or 11.9								
	absolute uncertainties in $1/I$ from ± 2 (or ± 1) to ± 0.2 , ± 0.3 or ± 0.4 . Allow a mixture of significant figures.	1						
2(c)(i)	Six points plotted correctly. Must be within half a small square. Diameter of points must be less than half a small square.	1						
	Error bars in $1/I$ plotted correctly. All error bars to be plotted. Length of bar must be accurate to less than half a small square and symmetrical.	1						
2(c)(ii)	Line of best fit drawn. Points must be balanced. Line should pass to the left of (0.50, 29.6) and line should pass between (0.210, 16) and (0.225, 16).	1						
	Worst acceptable line drawn (steepest or shallowest possible line that passes through all the error bars). All error bars must be plotted.	1						

PUBLISHED

Question	Answer	Marks
2(c)(iii)	Gradient determined with clear substitution of points from line of best fit into $\Delta y/\Delta x$. Distance between points must be at least half the length of the drawn line.	1
	uncertainty = gradient of line of best fit – gradient of worst acceptable line or uncertainty = $\frac{1}{2}$ (steepest worst line gradient – shallowest worst line gradient)	1
2(c)(iv)	y-intercept determined by substitution into $y = mx + c$.	1
	y-intercept of worst acceptable line determined by substitution into $y = mx + c$. uncertainty = y-intercept of line of best fit – y-intercept of worst acceptable line or uncertainty = $\frac{1}{2}$ (steepest worst line y-intercept – shallowest worst line y-intercept) Do not allow if false origin used.	1
2(d)(i)	E calculated using gradient. Correct substitution of numbers required. $E = \frac{470}{\text{gradient}} = \frac{470}{\mathbf{(c)(iii)}}$	1
	r calculated using y-intercept. Correct substitution of numbers required. $r = E \times \text{y-intercept}$	1
	E and r determined using correct method with: <ul style="list-style-type: none"> • Unit of E with correct power of ten – e.g. V, $A\Omega$ • Unit of r with correct power of ten – e.g. Ω, VA^{-1} • E and r given to 2 or 3 significant figures. 	1

PUBLISHED

Question	Answer	Marks
2(d)(ii)	<p>Percentage uncertainty in r determined. Correct substitution of numbers required.</p> <p>%uncertainty in gradient + %uncertainty in R (1.06%) + %uncertainty in y-intercept or %uncertainty in E + %uncertainty in y-intercept</p> <p>Maximum/minimum methods:</p> <p>$\max r = \max y\text{-intercept} \times \max E$</p> <p>$\max r = \max y\text{-intercept} \times \frac{\max R(475)}{\min \text{gradient}}$</p> <p>$\min r = \min y\text{-intercept} \times \min E$</p> <p>$\min r = \min y\text{-intercept} \times \frac{\min R(465)}{\max \text{gradient}}$</p>	1